


Power Beam

TUNGSTEN
12kW/10kW




L12010TPB

ACCESSORIES



Electronic Dimmer
24kW / 12kW




Ø741 Scrims
with Bag



Transport Case

PHOTOMETRIC DATA



10m 25m 50m 75m 100m

12kW

Spot	Lux	32400	5184	1296	576	324
	Beam Ø	1.3 m	3.25 m	6.5 m	9.74 m	12.99 m
Flood	Lux	6800	1088	272	121	68
	Beam Ø	4.29 m	10.74 m	21.47 m	32.21 m	42.95 m

FILMGEAR®

LAMPHEAD CONTENTS

Lamp Housing with

- High Reflective Parabolic Glass Mirror
- On-Off Switch
- Inlet Cable 1.5m (Bare End)
- Stirrup with Ø28mm Spigot
- # Exclude Lamp Bulb

SPECIFICATIONS

Identity No.	L12010TPB (220V)
Capacity	12,000W / 10,000W
Voltage	200 - 240V AC
Protective Lens	Ø645mm
Lamp Type	12kW/10kW SE
Color Temp.	3200K
Lamp Holder	G38
Stirrup	Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 23
Max. Surface Temp.	220 °C
Max. Ambient Temp.	45 °C
Min. Distance to Illuminated Object	8 m
Min. Distance to Flammable Object	2 m
Operating Range	+45° ~ 0° ~ -45°
Weight (lamphead)	50 kg

DIMENSIONS (mm)

