

Power Beam

DAYLIGHT

9kW/6kW

FILMGEAR®

L09060DPB




LAMPHEAD CONTENTS

Lamp Housing with


- High Reflective Parabolic Glass Mirror
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm Spigot

Exclude Lamp Bulb


ACCESSORIES




Electronic Ballast
9kW / 6kW



Ø741 Scrims with Bag



Head to Ballast Cable
(10m or 15m)




Transport Case

SPECIFICATIONS

Identity No.	L09060DPB
Capacity	9,000W / 6,000W
Lamp Bulb Voltage	160V / 125V
UV Protective Lens	Ø645mm
Lamp Type	CSR 9000W/SE/HR or HMI 9000W/SE or HMI 6000W/SE
Color Temp.	5600K
Lamp Holder	GX38
Stirrup	Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 23
Max. Surface Temp.	220 °C
Max. Ambient Temp.	45 °C
Min. Distance to Illuminated Object	15m
Min. Distance to Flammable Object	1.5m
Operating Range	+45° ~ 0° ~ -45°
Weight (lamphead)	55 kg

PHOTOMETRIC DATA



9kW	Spot	Lux	427500	68400	17100	7600	4275
		Beam Ø	0.61 m	0.61 m	0.61 m	0.61 m	0.61 m
Flood		Lux	43000	6880	1720	764	430
		Beam Ø	2.40 m	6.00 m	12.01 m	18.01 m	24.02 m

DIMENSIONS (mm)

